

## VEEDOL MULTIGRADE PLUS 15W-40

**Description** **Veedol Multigrade Plus 15W-40** is a modern multifunctional motor oil, produced with high quality solvent refined base oils and modern additives to obtain the following properties:

- Strong detergency and dispersion power
- Strong resistance against oxidation
- Strong protection against wear
- Strong protection against corrosion and foaming
- High and stable viscosity index
- Low tendency to evaporation

**Application** **Veedol Multigrade Plus 15W-40** is recommended for use in petrol, diesel, and LPG engines, with or without turbo-charging, in passenger cars and delivery vans.

**Performance Specifications** API SL/CF  
ACEA A3/B4-12  
MB-Approval 229.1

<b>Typicals Properties</b>	Density at 15 °C, kg/l.....	0,883
	Viscosity -20 °C, mPa.s.....	.6600
	Viscosity 40 °C, mm <sup>2</sup> /s.....	110,60
	Viscosity 100 °C, mm <sup>2</sup> /s.....	14,70
	Viscosity Index.....	137
	Flash Point COC, °C.....	230
	Pour Point, °C.....	-30
	Total Base Number, mgKOH/g.....	10,2
	Sulphate Ash, %.....	1,29

**Veedol International B.V.**

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.