The Professional's Choice in Motor Oil... For over a century

Revision date: 06.11.2015

VEEDOL POWERTRON PLUS 5W-40

Description

Veedol Powertron Plus 5W-40 is a extremely modern, synthetic, universal motor oil based on specially selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- High and very stable viscosity index
- · High resistance against shearing
- Fast cold start
- · Very strong resistance against oxidation
- Safe lubrication film at very high temperatures
- Very good detergency and dispersion
- · Very strong protection against wear, corrosion and foaming

Application

Veedol Powertron Plus 5W-40 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

Performance Specifications

API SN/CF ACEA A3/B4-12

MB-Approval 229.3

Approved under VW 502.00/505.00

Meets the requirements of: Renault RN0700/RN0710

Fiat 9.55535-M2 Porsche A40

BMW Longlife-01

GM LL-B-025

MB 226.5

Typicals Properties

Density at 15 °C, kg/l	0,858
Viscosity -30 °C, mPa.s	6110
Viscosity 40 °C, mm²/s	87,40
Viscosity 100 °C, mm²/s	14,40
Viscosity Index	172
Flash Point COC, °C	223
Pour Point, °C	33
Total Base Number, mgKOH/g	10,5
Sulphate Ash, %	1.33

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

TM Registered trademark of Veedol International UK