

VEEDOL POWERTRON ULTRA 5W-40

Description **Veedol Powertron Ultra 5W-40** motor oil is developed according to the most recent technology and based on specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- High resistance against shearing
- Fast cold start
- Safe lubrication film at very high temperatures
- Reduced formation of combustion ashes
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

Application **Veedol Powertron Ultra 5W-40** motor oil is specially developed for passenger car unit injector diesel engines. Moreover this lubricant is very suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEMs and thus has a wide application.

Performance Specifications API SN/CF
ACEA C3-12
MB-Approval 229.51
Approved under VW 502.00/505.00/505.01
BMW Longlife-04
Meets the requirements of:
MB 229.31/226.5
Ford M2C917-A
Porsche A40
Renault RN0700/RN0710
Dexos 2
Fiat 9.55535-S2

Typicals Properties	Density at 15 °C, kg/l.....	0,850
	Viscosity -30 °C, mPa.s.....	5500
	Viscosity 40 °C, mm ² /s.....	82,80
	Viscosity 100 °C, mm ² /s.....	14,00
	Viscosity Index.....	175
	Flash Point COC, °C.....	232
	Pour Point, °C.....	-42
	Total Base Number, mgKOH/g.....	7,4
	Sulphate Ash, %.....	0,77

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.