

VEEDOL DIESEL STAR FLEET HS 10W-40

Description **Veedol Diesel Star Fleet HS 10W-40** is based on the officially approved formulas, using the same high-quality additives, but with equivalent alternative base oils. It is therefore a equivalent product in terms of quality, with a performance level corresponding to the originally approved products. However no field test has been conducted to validate the performance and therefore it is claimed only to 'meet the requirements of' as below.

Application This engine lubricant is used for gasoline and diesel engines (normally- or turboaspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used when fuels with relatively high sulphur contents are involved. This special quality of engine oil is mainly developed to allow extended oil drain intervals and to prevent "bore polishing" (=cylinder-wear) in diesel engines. This product is suitable for application in Euro 4 and Euro 5 engines.

Performance Specifications API CI-4/SL
ACEA A3/B4-12, E7-12
Meets the requirements of:
MB 228.3/229.1
MAN M 3275, Volvo VDS-3
Renault VI RLD/RLD-2, MTU Type 2
Cummins CES 20076/20077/20078
Mack EO-N/EO-M Plus
Global DHD-1
Cat ECF-1-a/ECF-2
Deutz DQC III-10
Detroit Diesel 93K215
ZF TE-ML 07C

Typicals Properties

Density at 15 °C, kg/l.....	0,867
Viscosity -25 °C, mPa.s.....	5800
Viscosity 40 °C, mm ² /s.....	85,81
Viscosity 100 °C, mm ² /s.....	13,80
Viscosity Index.....	156
Flash Point COC, °C.....	222
Pour Point, °C.....	-39
Total Base Number, mgKOH/g.....	10,7
Sulphate Ash, %.....	1,36

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.