

VEEDOL MAX-PRO EXTRA 10W-40

- Description** **Veedol Max-Pro Extra 10W-40** is a modern diesel engine oil based on advanced additive technology combined with special synthetic base oils. This results in the following properties for this engine oil:
- Very powerful detergency which prevents deposits in the engine
 - Very strong dispersion that prevents precipitation and sludge formation
 - Powerful action against corrosion and foaming
 - High viscosity index
 - High sulphated ash number
 - Powerful activity against wear resulting in strongly reduced wear of piston rings and cylinder liners
 - Longer oil drain intervals

Application This lubricant has mainly been developed for heavy duty diesel engines even under the toughest operation conditions and for all year round use. This product is very suitable for Euro 2 to Euro 6 engines in combination with different diesel fuel qualities. This engine oil is also suitable for application in engines with or without exhaust catalyts.

Performance Specifications API CF
ACEA E4-12, E7-12
MAN M 3277
MB-Approval 228.5
Scania LDF-3
Volvo VDS-3
Renault VI RLD-2
Mack EO-N
Meets the requirements of:
Renault VI RXD

Typicals Properties	Density at 15 °C, kg/l.....	0,869
	Viscosity -25 °C, mPa.s.....	.6610
	Viscosity 40 °C, mm ² /s.....	88,30
	Viscosity 100 °C, mm ² /s.....	13,40
	Viscosity Index.....	153
	Flash Point COC, °C.....	220
	Pour Point, °C.....	-36
	Total Base Number, mgKOH/g.....	15,9
	Sulphate Ash, %.....	1,80

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.