

VEEDOL MAX-PRO PLUS 10W-40

Description **Veedol Max-Pro Plus 10W-40** is a top quality diesel engine oil based on the latest additive technology combined with very special base oils.

This engine oil has the following properties:

- Very powerful detergency prevents deposits in the engine
- Very strong dispersion that prevents from precipitation and sludge formation
- Powerful activity against wear, corrosion and foaming
- High and stable viscosity index
- Low sulphated ash number
- Prolonged oil drain intervals

Application This lubricant has been developed for heavy diesel engines under the toughest operating conditions and for use all the year round. This product is very suitable for Euro 4 and Euro 5 engines without particulate filters and for most engines with exhaust gas emission systems. This engine oil is also developed to (in keeping with the official standards) allow very long extended oil drain intervals and to prevent "bore-polishing".

Performance Specifications

API CI-4
ACEA E4-12, E7-12
MB-Approval 228.5
MAN M 3377/M 3277

Meets the requirements of:
Volvo VDS-3
Renault VI RLD-2, RXD
Mack EO-N
MTU Type 3
Deutz IV-10
Mack EO-M Plus
Cummins CES 20078
Global DHD-1
Detroit Diesel 93K215

Typicals Properties

Density at 15 °C, kg/l.....	0,865
Viscosity -25 °C, mPa.s.....	.6350
Viscosity 40 °C, mm ² /s.....	95,90
Viscosity 100 °C, mm ² /s.....	14,00
Viscosity Index.....	148
Flash Point COC, °C.....	226
Pour Point, °C.....	-36
Total Base Number, mgKOH/g.....	12,6
Sulphate Ash, %.....	1,47

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.