

VEEDOL MAX-PRO SPECIAL LSP 15W-40

Description **Veedol Max-Pro Special LSP 15W-40** is a Heavy Duty engine oil formulated with unique low SAPS high performance additives in combination with special selected base oils. This multigrade engine oil fulfills the latest requirements of OEM's for use in high speed four stroke diesel engines of the most recent models and has the following properties:

- Meets or exceeds the requirement of the current lowest emission standards
- Excellent cold start properties
- Very good shear stability
- Improved oxidation resistance
- Very strong dispersion, therefore the deposits and sludge are restricted to a minimum
- Excellent properties against wear, corrosion and foaming
- Lower oil consumption

Application This Heavy Duty engine oil is suitable for use in both on-road and off-highway applications. This engine oil contributes to lower exhaust emission and particulate levels, improving the lifetime of emission control systems. This product complies with and exceeds the requirements of API CJ-4. By meeting the requirements of OEM's in Europe and North America this product has a wide choice of application possibilities. This product can be applied in Euro 5 engines with SCR exhaust gas system and in Euro 3 and Euro 4 engines when indicated by the manufacturer.

Performance Specifications

API CJ-4/SM
ACEA E7-12, E9-12
Volvo VDS-4
Renault VI RLD-3
Mack EO-O Premium Plus

Meets the requirements of:
MB 228.31
MAN M 3575
Cat ECF-2/ECF-3
Cummins CES 20081
Detroit Diesel 93K218
JASO DH-2
Global DHD-1
MTU Type 2.1
Deutz DQC III-10 LA

Typicals Properties

| | |
|---|--------|
| Density at 15 °C, kg/l..... | 0,874 |
| Viscosity -20 °C, mPa.s..... | 6880 |
| Viscosity 40 °C, mm ² /s..... | 108,70 |
| Viscosity 100 °C, mm ² /s..... | 14,50 |
| Viscosity Index..... | 137 |
| Flash Point COC, °C..... | 232 |
| Pour Point, °C..... | -36 |
| Total Base Number, mgKOH/g..... | 8,0 |
| Sulphate Ash, %..... | 0,92 |

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.