

VEEDOL MAX-PRO ULTRA 5W-30

Description **Veedol Max-Pro Ultra 5W-30** is an advanced fuel economy diesel engine oil based on the latest additive technology, combined with very special base oils.

This engine oil has the following properties:

- Very powerful detergency prevents deposits in the engine
- Very strong dispersion that prevents from precipitation and sludge
- Powerful activity against corrosion and foaming
- High and stable natural viscosity index
- High sulphated ash number
- Powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners
- Lower fuel consumption

Application This fuel saving lubricant has mainly been developed for heavy diesel engines even under the toughest operation conditions and all the year round. This product is very suitable for Euro 3, 4 and 5 engines in combination with diesel fuel with a relatively low sulphur content. This engine oil is also developed to allow (in keeping with the official standards) extended oil drain intervals.

Performance Specifications

API CI-4
ACEA E4-12, E7-12
MB-Approval 228.5
MAN M 3277
Volvo VDS-3
Mack EO-N
Renault VI RLD-2

Meets the requirements of:
DAF HP1/HP2
Cat ECF-2
Cummins 20076/20078
Deutz DQC IV-10
Mack EO-M Plus
MTU Type 3
Renault VI RXD
Global DHD-1
JASO DH-1
Scania LDF
MAN M 3377

Typicals Properties

Density at 15 °C, kg/l.....	0,855
Viscosity -30 °C, mPa.s.....	6420
Viscosity 40 °C, mm ² /s.....	71,60
Viscosity 100 °C, mm ² /s.....	12,17
Viscosity Index.....	168
Flash Point COC, °C.....	224
Pour Point, °C.....	-39
Total Base Number, mgKOH/g.....	12,2
Sulphate Ash, %.....	1,35

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.