

VEEDOL GREASE EPS

Description

Veedol Grease EPS is a lithium thickened lubricating grease based on mineral oil. The grease contains antioxidants, corrosion inhibitors and EP/AW additives.

This product is a state-of-the-art multipurpose EP grease which can be used in various applications within given temperature limits. This lubricating grease offers good mechanical stability and load carrying capacity, making it suitable for heavily loaded bearings.

Features & Benefits

Veedol Grease EPS is a high quality multipurpose grease that can be used in both industrial and automotive applications. The grease is suitable for a wide range of plain and rolling bearings.

Classification

ISO 12924	L-XC(F)CHB2
DIN 51502	KP2K-30

Typical Technical Data

Thickener		Lithium
Base fluid		Mineral oil
Texture		Smooth
Colour	Visual	Brown
NLGI Grade	ASTM D 217	2
Dropping point	IP 396	> 180°C
Base oil viscosity at 40°C	ASTM 7152	195 mm ² /s
Base oil viscosity at 100°C	ASTM 7152	15 mm ² /s
Penetration 60 strokes	ISO 2137	265 - 295
4-ball weld load	DIN 51350:4	2600 N
Water resistance at 90°C	DIN 51807:1	1
Water wash out at 79°C	ISO 11009	< 10 %
Emcor dist water ISO	11007	0 - 0
Flow Pressure at -30°C	DIN 51805 mod	< 1400 mbar
SKF R2F B at 120°C	SKF	Pass
Density	IP 530	905 kg/ m ³
Temperature range		-30°C to +120°C (Max +130°C)

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.