

Revision date: 06.11.2015

| | VEEDOL ATF II-D |
|-------------------------------|---|
| Description | Veedol ATF II-D is a very high grade automatic transmission fluid formulated with solvent refined base oils and a number of select additives to obtain the following properties: High and stable viscosity index Very low pour point Very good stability against oxidation Positive activity against wear, corrosion and foaming Specific friction properties Perfect compatibility with seals and non-ferro metals Red coloured |
| Application | This fluid is used for automatic gearboxes, power steering units, torque converters and other equipment for which an ATF Dexron II-D fluid is required. |
| Performance Specifications | MB-Approval 236.7 MAN 339 Typ Z1 Meets the requirements of: GM Dexron IID Allison C4 Ford M2C138-CJ/166-H Ford SQM-2C9010-A ZF TE-ML 09/11A/14A Cat TO-2 Voith 55.6335 (G607) Renk MAN 339 Typ V1 |
| Typicals Properties | Density at 15 °C, kg/l |

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final procuct-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.