

VEEDOL ATF III-AP

Description **Veedol ATF III-AP** is a synthetic automatic transmission fluid, based on synthetic base oils and formulated with special friction modifiers to obtain the following properties:

- Very high and stable viscosity index
- Very low pour point
- Excellent stability against oxidation
- Specific friction properties and consequently low noise and smooth switching
- Compatible with synthetic seals
- Quick oil provision at cold start conditions
- Very strong protection against wear, corrosion and foaming

Application This fluid may be used for the automatic transmissions, of a wide range of cars including Japanese cars with the specifications mentioned below. It is recommended to follow the instructions of the manufacturer.

Performance Specifications

Meets the requirements of:	Mazda ATF M-V
MB 236.1/236.6/236.7/236.8/236.9/236.10	Hyundai/Kia SP-II/SP-III
BMW 7045E/8072B	Suzuki ATF 3314
GM Dexron IID/IIIE/IIIG/IIIH, TASA	Subaru ATF/ATF 5AT/ATF HP/Dexron II
Allison C4/TES-228	Isuzu Besco ATF II/III
Toyota ATF T-III/T-IV/D-II/WS	Ford Mercon/M2C 138CJ/166H/922A1/924A
Nissan Matic Fluid C/D/J/K	Aisin Warner JWS 3309/3324
Honda ATF-Z1 (except in CVT's)	VAG G-055-025
JASO M 315-2013 Type 1A	Volvo 1161540
Chrysler ATF +3/ATF +4	ZF TE-ML 09/11A/11B

Typicals Properties

Density at 15 °C, kg/l.....	0,846
Viscosity 40 °C, mm ² /s	36,60
Viscosity 100 °C, mm ² /s	7,20
Viscosity Index.....	165
Flash Point COC, °C	212
Pour Point, °C.....	-48
Total Base Number, mgKOH/g	2,7

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.