

## VEEDOL EP GEAR OIL 80W

**Description** **Veedol EP Gear Oil 80W** is a mineral lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special EP additives to obtain the following properties:

- Good resistance against oxidation
- Good rust preventing, anti-corrosion and foam inhibition
- Low pourpoint
- Good Extreme Pressure (EP-) properties

**Application** This gear oil should be used in hypoid differentials, gearboxes and other transmissions, for which an EP transmission oil is advised.

**Performance Specifications** API GL-4  
Mil-L-2105  
Meets the requirements of:  
MB 235.1  
ZF TE-ML 17A  
MAN 341 Typ Z2/E1

<b>Typicals Properties</b>	Density at 15 °C, kg/l.....	0,885
	Viscosity 40 °C, mm <sup>2</sup> /s .....	77,00
	Viscosity 100 °C, mm <sup>2</sup> /s .....	9,50
	Viscosity Index.....	98
	Flash Point COC, °C .....	205
	Pour Point, °C.....	-35

**Veedol International B.V.**

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

<sup>TM</sup> Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.