



TM



The Professional's Choice in Motor Oil...
For over a century

Revision date: 06.11.2015

VEEDOL GEAR OIL LD 75W-80

Description **Veedol Gear Oil LD 75W-80** is a synthetic lubricating oil for mechanical transmissions, formulated with high quality synthetic base oils and special EP additives to obtain the following properties:

- Excellent thermal stability
- Very high activity against wear, corrosion and foam
- Low pour point
- Very high quality EP-properties
- Good clutch-switch performance at low temperatures
- Long durability
- Fuel economy

Application This gear oil is specially developed for gearboxes under very heavy duty conditions, together with high temperatures. This oil can also be used for extended drain intervals.

Performance Specifications API GL-4
Mil-L-2105
MAN 341 Typ Z4/E3
ZF TE-ML 01L/02L/16K
Meets the requirements of:
DAF
Volvo 97305
Eaton Europe (extended drain)
Iveco
Renault

Typicals Properties

Density at 15 °C, kg/l.....	0,858
Viscosity 40 °C, mm ² /s	65,00
Viscosity 100 °C, mm ² /s	10,00
Viscosity Index.....	156
Flash Point COC, °C	218
Pour Point, °C.....	-45

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.