

VEEDOL GEAR OIL SPECIAL HD 75W-90

Description **Veedol Gear Oil Special HD 75W-90** is a semi-synthetic lubricating oil for mechanical transmissions, formulated with high quality solvent refined and synthetic base oils and special EP additives to obtain the following properties:

- Excellent resistance against oxidation
- Very high activity against wear, corrosion and foam
- Low pour point
- Very good EP-properties
- Good clutch-switch performance at low temperatures
- Fuel economy

Application This gear oil is used in gearboxes under very heavy duty conditions and should be used in gearboxes where mineral EP gear oils give switch problems.

Performance Specifications API GL-4/5
Mil-L-2105
Meets the requirements of:
VW 501.50

| | | |
|----------------------------|--|-------|
| Typicals Properties | Density at 15 °C, kg/l..... | 0,879 |
| | Viscosity 40 °C, mm ² /s | 83,00 |
| | Viscosity 100 °C, mm ² /s | 15,50 |
| | Viscosity Index..... | 188 |
| | Flash Point COC, °C | 180 |
| | Pour Point, °C..... | -45 |

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

TM Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.