

VEEDOL GEAR OIL SPECIAL MP 75W-90

Description **Veedol Gear Oil Special MP 75W-90** is a semi-synthetic lubricating oil for mechanical transmissions, formulated with high quality solvent refined synthetic base oils and special EP-additives to obtain the following properties:

- Good resistance against oxidation
- Good rust preventing, anti-corrosion and foam inhibiting properties
- Low pourpoint
- Good Extreme Pressure (EP-) properties
- Good clutch-switch performance at low temperatures
- Fuel economy

Application This multipurpose gear oil should be used in hypoid differentials, gearboxes and other transmissions for which an EP transmission oil is advised and which give switch problems.

Performance Specifications API GL-4/MT-1

Typicals Properties	Density at 15 °C, kg/l.....	0,868
	Viscosity 40 °C, mm ² /s	76,30
	Viscosity 100 °C, mm ² /s	14,20
	Viscosity Index.....	194
	Pour Point, °C.....	-42

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.