

VEEDOL HYDRAULIC OIL 32

Description **Veedol Hydraulic Oil 32** is a high grade EP hydraulic oil based on selected, solvent refined base oils with special, with special additives to obtain the following properties:

- Excellent protection against wear
- Very good protection against rust and corrosion
- Excellent stability against oxidation
- Very good demulsification properties
- Very good deaerating and foam-suppressing properties
- Good compatibility with seals and gaskets made from synthetic material
- Low pour point

Application This type of hydraulic fluid may be used for heavy duty hydraulic equipment, as well as for light duty gear boxes and bearings. This hydraulic oil may also be used for lubrication systems, general lubrication and vacuum pumps (with the exclusion of turbines). This fluid is **NOT** compatible in systems, containing parts or equipment with a silver lining.

Performance Specifications Meets the requirements of:
DIN 51524-2 HLP
AFNOR NF E 48-603 HM
ISO 11158 HM
ASTM D 6158 HM
Denison HF-0/HF-1/HF-2
Cincinnati Machine P-68
Eaton Brochure 694 for 35VQ25A
GM LS-2

Typicals Properties	Density at 15 °C, kg/l.....	0,872
	Viscosity 40 °C, mm ² /s	32,00
	Viscosity 100 °C, mm ² /s	5,52
	Viscosity Index.....	108
	Flash Point COC, °C	205
	Pour Point, °C.....	-30
	Acid number, mgKOH/g.....	0,40
	Sulphate Ash, %	0,06

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.