

The Professional's Choice in Motor Oil... For over a century

Revision date: 06.11.2015

VEEDOL SINTRON V 0W-30

Description

Veedol Sintron V 0W-30 is a fully synthetic motor oil produced with advanced new technology additives to obtain the following properties:

- Lower fuel consumption
- Very high viscosity index
- High resistance against shearing
- Fast cold start
- · Safe lubrication film at high temperatures
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

Application

This fuel saving, fully synthetic motor oil is specially developed for use in petrol and diesel engines of VW passenger cars and delivery vans with extended oil drain intervals. This oil is also applicable in those engines, where the specifications as stated below are requested.

This oil is not applicable in those cases, where a VW-Norm 503.01 is requested.

Performance Specifications

ACEA A1/B1-04, A5/B5-04 Meets the requirements of: VW 503.00/506.00/506.01

Typicals Properties

Density at 15 °C, kg/l	0,857
Viscosity -30 °C, mPa.s	3100
Viscosity 40 °C, mm²/s	55,30
Viscosity 100 °C, mm²/s	10,10
Viscosity Index	174
Flash Point COC, °C	226
Pour Point, °C	50
Total Base Number, mgKOH/g	10,2
Sulphate Ash, %	1,28

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

TM Registered trademark of Veedol International UK