

## VEEDOL SINTRON ULTRA 0W-40

**Description** **Veedol Sintron Ultra 0W-40** is a modern universal full-synthetic motor oil produced with high quality synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- High and very stable viscosity index
- High resistance against shearing
- Fast cold start
- Safe lubrication film at very high temperatures
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

**Application** This universal synthetic motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below. Its low viscosity enables the use of this motor oil under extreme conditions.

**Performance Specifications** API SN/CF  
ACEA A3/B4-12  
Meets the requirements of:  
MB 229.3/226.5  
VW 502.00/505.00  
BMW Longlife-01  
Renault RN0700/RN0710  
Porsche A40

<b>Typicals Properties</b>	Density at 15 °C, kg/l.....	0,846
	Viscosity -35 °C, mPa.s.....	6000
	Viscosity 40 °C, mm <sup>2</sup> /s.....	83,70
	Viscosity 100 °C, mm <sup>2</sup> /s.....	14,00
	Viscosity Index.....	173
	Flash Point COC, °C.....	232
	Pour Point, °C.....	-46
	Total Base Number, mgKOH/g.....	10,5
	Sulphate Ash, %.....	1,33

### Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.