

VEEDOL ATF III-H

Description **Veedol ATF III-H** is a very high grade automatic transmission fluid formulated with solvent refined base oils and a number of select additives to obtain the following properties:

- Very high and stable viscosity index
- Very low pour point
- Very good stability against oxidation
- Positive activity against wear, corrosion and foaming
- Specific friction properties
- Perfect compatibility with seals and non-ferro metals
- It is Red coloured

Application This fluid is used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron III-H fluid is required.

Performance Specifications Meets the requirements of:
GM Dexron IIIH
MB 236.1 / 236.5
MAN 339 Typ Z1/V1
ZF TE-ML 09B/11B/14A
Ford Mercon
Allison C4 / TES-389
Cat TO-2
Voith 55.6335
Volvo 97341

Typicals Properties	Density at 15 °C, kg/l.....	0,853
	Viscosity 40 °C, mm ² /s	34,40
	Viscosity 100 °C, mm ² /s	7,50
	Viscosity Index.....	194
	Flash Point COC, °C	220
	Pour Point, °C.....	-48
	Total Base Number, mgKOH/g	2,6

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

TM Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.