

## VEEDOL PRIMA SUPER TRACTOR OIL UNIVERSAL

**Description** **Veedol Prima Super Tractor Oil Universal** is an up-to-date multifunctional lubricating oil for agricultural and earthmoving equipment, formulated with top-grade solvent refined base oils and additives, to obtain the following properties:

- powerful dispersion and detergency
- resistance to wear, corrosion and foaming
- very strong resistance to oxidation
- excellent extreme pressure properties
- high and stable viscosity index

**Application** This multifunctional lubricant (\*) has been developed to achieve one single lubricating oil that is able to lubricate:

- gasoline engines
- diesel engines (with or without turbo-charging)
- transmissions also ("wet" brakes)
- hydraulic systems

(\*) a so-called *Super Tractor Oil Universal = STOU*

**Performance Specifications**

API SF/CG-4/GL-4  
ACEA E3-96, Mil-L-2104D  
Meets the requirements of  
Ford M2C159-C  
Massey Ferguson CMS M1139/M1144/M1145  
MB 227.1  
John Deere J20C  
ZF TE-ML 06B/07B  
Massey Ferguson CMS M1135/M1143  
Cat TO-2  
Allison C4  
Ford M2C134-D

**Typicals Properties**

Density at 15 °C, kg/l.....	0,884
Viscosity -20 °C, mPa.s.....	6000
Viscosity 40 °C, mm <sup>2</sup> /s.....	76,60
Viscosity 100 °C, mm <sup>2</sup> /s.....	10,50
Viscosity Index.....	122
Flash Point COC, °C.....	220
Pour Point, °C.....	-36
Total Base Number, mgKOH/g.....	11,3
Sulphate Ash, %.....	1,45

### Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.