



VEEDOL UTTO WET BRAKE

Description **Veedol UTTO Wet Brake** is a very high quality universal hydraulic and transmission oil formulated with unconventional base oils and selected additives to obtain the following properties:

- high and stable viscosity index
- very low pour point
- very good stability against oxidation
- a high thermal stability
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefor applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

Application This very high quality universal tractor transmission oil (UTTO) has been developed for the heavy loaded hydraulics and transmissions, with or without wet brakes, of most generally used agricultural and road-construction equipment.

Performance Specifications Meets the requirements of
API GL-4
Volvo WB 102
Massey Ferguson M1141/M1143/M1145
ZF TE-ML 03E/05F/06K
Allison C3/C4, John Deere J20A
Cat TO-2
Case MS1207/MS1209

Typicals Properties	Density at 15 °C, kg/l.....	0,856
	Viscosity 40 °C, mm ² /s.....	41,00
	Viscosity 100 °C, mm ² /s.....	7,70
	Viscosity Index.....	160
	Flash Point COC, °C.....	224
	Pour Point, °C.....	-42

Veedol International B.V.

Kabelweg 21 | 1014 BA | Amsterdam | The Netherlands | Tel: +31(0)20-3584607 | Fax: +31(0)20-3313266

™ Registered trademark of Veedol International UK

The data mentioned in this product information sheet is meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.